



Ultimate painting solution for your dream home

BERGER XPRESS SEALER



PRODUCT DESCRIPTION

Berger XPress Sealer is specially designed with acrylic methacrylic ester based polymer having excellent alkali resistance properties to stop migration of ions to the top coat. Its unique alkali-cation absorption technology makes it professional choice due to faster application feasibility even in highly alkaline condition. It enables faster project completion and can be applied on freshly prepared concrete & masonry surface within 06 to 07 days.



ANTI FUNGAL



BARRIER TO SALT MIGRATION



EXCELLENT TOP COAT ADHESION



OUTSTANDING DURABILITY



IMPROVED FORMULA WITH ALKALI-CATION ABSORPTION TECHNOLOGY



PRODUCT INFORMATION

PACK SIZES



0.9 Ltr

3.6 Ltr

18 Ltr

COVERAGE

WALL

1 COAT
150-155 SFT/
Ltr/Coat



*Coverage mentioned is based on lab tests conducted under controlled environment
**Actual coverage is dependent on factors such as surface condition, application method, and application condition

UNIQUE FEATURE

WITHIN 7 DAYS APPLICATION

Can be applied after 6-7 days of plaster preparation

SURFACE PREPARATION



Recommended Surfaces



Concrete Stone



Hard Board



Interior Cement Plaster



Brick Asbestos



False Ceilings



Surface Preparation Method

Newly prepared plastered surface is allowed to mature for a period of only 06 to 07 days of drying. Chalk joints and fill holes where necessary. Ensure that the surface is free from loose particles and any greasy/oily substance by cleaning the surface through rubbing with emery paper or wire brush.

Berger offers a complete range of surface treatment solutions, please call 08000-123456 or visit your nearest Berger Experience Zone for more information.



METHOD OF APPLICATION



Fill the holes in the walls



Clean the walls by rubbing with sandpaper



Apply one coat of 100% thinned Berger XPress Sealer as the prime coat



Let the sealer dry for 7-8 hours before top coat application



MIXING RATIOS



For Brush - Sealer : Water = 1 : 1
For Roller - Sealer : Water = 1 : 1
(By volume)



ADDITIONAL INFORMATION

- ◆ After plastering the interior walls of the house, dry the wall for atleast 7 days before using Berger XPress Sealer
- ◆ If you use the sealer on the inner wall, give 8-12 weeks to dry the moisture on the outer wall
- ◆ If the wall contains salt or there exists any algae or fungus on it, special treatment is required
- ◆ Do not apply at temperature below 10°C (50°F)



ACCOMPANYING PRODUCT



SHEEN SCALE AND SHADE



Robbialac Wall Putty



Breathe Easy Wall Putty



W/C Touch Putty

Matt Finish

Egg Shell

Soft Sheen/Satin

High Sheen

Gloss

Super Gloss

***Only available in White**



PRODUCT SPECIFICATION




TYPE OF CURE

Coalescence



SHELF LIFE



VISCOSITY AT 30°C



TOUCH DRY



PIGMENTATION

TITANIUM DIOXIDE MAGNESIUM SILICATE ALUMINUM SILICATE



METHOD OF APPLICATION



ROLLER

BRUSH



HARD DRY



SOLVENT



WATER



ETHYLENE GLYCOL




VOC

< 10 g/Ltr
(Theoretical value)



AROMATIC CONTENT



POT LIFE AFTER THINNING



RECOMMENDED THINNER



POTABLE WATER

*Please refer to MSDS for safety information

The above information is given to the best of our knowledge based on laboratory tests and practical experience. However, since we cannot anticipate or control the many conditions under which our products may be applied, we can only guarantee the quality of the product itself. We reserve the right to alter the given data without prior notice. Covering capacity is indicated on the basis of results obtained on a prepared smooth surface.