



Ultimate painting solution for your dream home

# BREATHE EASY WATER SEALER



## PRODUCT DESCRIPTION

Breathe Easy Water Sealer is a new invention in the arena of primer for plastered wall with healthy home concept. It is a Volatile Organic Compound (VOC) free product that provides a friendly environment and is odor free. It can seal and stop penetration of moisture from inside wall and keeps the topcoat finish unharmed. It conforms requirements of GS - II.



BIO FRESH



GREEN LABEL SINGAPORE



ENVIRONMENT FRIENDLY



ULTRA LOW VOC



## PRODUCT INFORMATION

### PACK SIZES



0.9 Ltr

3.6 Ltr

18 Ltr

### COVERAGE

WALL

1 COAT

160-165 SFT/Ltr



\*Coverage mentioned is based on lab tests conducted under controlled environment  
\*\*Actual coverage is dependent on factors such as surface condition, application method, and application condition

### UNIQUE FEATURE



Odor Free

## SURFACE PREPARATION



Recommended Surfaces



Concrete Stone



Interior  
Cement Plaster



Brick Asbestos



Cement Sheet



Surface Preparation  
Method

After plastering, allow the surface to dry for at least 8-12 weeks. Moisture content should be less than 15%. Before application, ensure that the surface is clean, dry, free from loose particles, dust, dirt, grease, wax, mould, fungal growth, etc. The product should not be applied on surfaces with continuous seepage or dampness.

Berger offers a complete range of surface treatment solutions, please call 08000-123456 or visit your nearest Berger Experience Zone for more information.



## METHOD OF APPLICATION



Clean surfaces by sanding with emery paper



Apply one coat of 100% thinned Breathe Easy Water Based Sealer and allow to dry for 4-6 hours



Apply two coats of Breathe Easy Wall Putty with a 6-8 hours interval



After overnight drying of Putty, sand smooth with emery paper



Apply one coat of 100% thinned Breathe Easy Water Based Sealer and let it dry for 24 hours



## MIXING RATIOS



**For Brush** - Sealer : Water = 1 : 1  
**For Roller** - Sealer : Water = 1 : 1  
(By volume)



## ADDITIONAL INFORMATION

- ◆ Use the thinned material within 12 hours
- ◆ Do not retain the thinned material beyond recommended time
- ◆ Do not stretch material beyond recommended coverage
- ◆ Do not apply at temperature below 10°C (50°F)



## ACCOMPANYING PRODUCT



Breathe Easy Wall Putty



## SHEEN SCALE AND SHADE

**Matt Finish**

Egg Shell

Soft Sheen/Satin

High Sheen

Gloss

Super Gloss

**\*Only available in White**



## PRODUCT SPECIFICATION



**TYPE OF CURE**

Coalescence



**SHELF LIFE**



In sealed container kept in cool & dry place



**VISCOSITY AT (30±1)°C**



110+/-2 KU (Sheen Krebs)



**TOUCH DRY**



**PIGMENTATION**

TITANIUM DIOXIDE

MAGNESIUM

ALUMINUM SILICATE



**METHOD OF APPLICATION**



ROLLER BRUSH



**HARD DRY**



(Recoat)



**SOLVENT**



WATER



PROPYLENE GLYCOL



**VOC**

≤ 05 g/L



**POT LIFE AFTER THINNING**



**AROMATIC CONTENT**



Below 50 ppm

\*Please refer to MSDS for safety information

The above information is given to the best of our knowledge based on laboratory tests and practical experience. However, since we cannot anticipate or control the many conditions under which our products may be applied, we can only guarantee the quality of the product itself. We reserve the right to alter the given data without prior notice. Covering capacity is indicated on the basis of results obtained on a prepared smooth surface.