



Ultimate painting solution for your dream home

# DUROCEM SOLID CEMENT



## PRODUCT DESCRIPTION

Durocem solid cement paint is an exceptional formulation of cement paint that can withstand extreme weather conditions and can be applied on both exterior and interior surfaces. It covers a large area through easy brush ability. It also gives a super durable finish with an unique aesthetic appeal and great value for money.



## PRODUCT INFORMATION

### PACK SIZES



5 Kg

20 Kg

40 Kg

### COVERAGE

WALL

2 COAT

45-55 SFT/kg  
(Depending on surface)

\*Coverage mentioned is based on lab tests conducted under controlled environment

\*\*Actual coverage is dependent on factors such as surface condition, application method, and application condition



### UNIQUE FEATURE



DRIES QUICKLY



ENHANCED WATER REPELLENCY

It dries quickly and does not require water curing

## SURFACE PREPARATION



Recommended Surfaces



All types of Concrete surface



Surface Preparation Method

**Surface preparation:** Surface must be clean, free from dust, grease, oil, chalk, mildew, etc. Chalk joints and fill holes where necessary. All old loose, flaking or peeling paint must be removed.

**For new walls:** After plastering, allow to dry the surface for at least 8-12 weeks. Moisture content should be 15% max (equipment for measuring moisture content: Protimeter). Wet the wall with clean water before application of Durocem.

**For old walls:** Previously painted surface with cement paint should be wire brushed and washed with water. After proper application of Durocem/cement-based paint on top of emulsion-based paint is prohibited due to adhesion issues (poor adhesion).

Berger offers a complete range of surface treatment solutions, please call 08000-123456 or visit your nearest Berger Experience Zone for more information.



## METHOD OF APPLICATION



1 Before application, rinse the wall properly with clean tap water to get desired coverage.



2 Add one portion of water with self curing Durocem and make a paste



3 After the temperature rising, add the second part of the water with paste for application



4 Apply the first coat and allow to dry at least 24 hrs for recoating



5 No need to cure by wetting after application of Self Curing Durocem



## MIXING RATIOS



**For Brush** - Paint : Water = 2 : 2  
**For Roller** - Paint : Water = 2 : 2  
(By volume)



## ADDITIONAL INFORMATION

- ◆ Before applying Durocem, the surface should be wetted properly
- ◆ Use the thinned material within 2-3 hours max
- ◆ Do not retain the thinned material beyond the recommended time
- ◆ Do not stretch material beyond recommended coverage
- ◆ Do not apply paint at direct sunlight or temperature below 50°F (10°C)
- ◆ Don't apply on hot and sunny side of the wall



## RECOMMENDED UNDERCOATS

N/A



## SHEEN SCALE

**Matt Finish**

Egg Shell

Soft Sheen/Satin

High Sheen

Gloss

Super Gloss



## PRODUCT SPECIFICATION



**TOUCH DRY**



**SHELF LIFE**



**METHOD OF APPLICATION**




ROLLER



BRUSH



**HARD DRY**



**PIGMENTATION**

TITANIUM DIOXIDE

IRON OXIDE YELLOW

IRON OXIDE BACK



**TYPE OF CURE**

Self Curing



**SOLVENT**



WATER

\*Please refer to MSDS for safety information

The above information is given to the best of our knowledge based on laboratory tests and practical experience. However, since we cannot anticipate or control the many conditions under which our products may be applied, we can only guarantee the quality of the product itself. We reserve the right to alter the given data without prior notice. Covering capacity is indicated based on results obtained on a prepared smooth surface.