



Ultimate painting solution for your dream home

# LUXURY SILK METALLIC FINISH



## PRODUCT DESCRIPTION

Luxury Silk Metallic Finish is the best quality water based metallic finish coating for interior application. It combines the best aesthetic appeal of silk with glitter particles that can give your wall a sparkling outlook. A special broad spectrum non-toxic and environment-friendly fungicide and biocide imparts strong anti-fungal and anti-bacterial properties to Silk Metallic. Its characteristic additives improve its cleanability & provide oil repellency which helps cleaning off all sorts of stains from the surface and gives the surfaces evergreen appearances & rich finish. It belongs exceptionally high scrub-resistance and can be cleaned easily with water or a mild solution of water and soap (not detergent) for easy maintenance.



ENVIRONMENT FRIENDLY  
LEAD FREE



EXCELLENT ALKALI & EFFLORESCENCE RESISTANCE



PHYSICAL BARRIER TO SALT MIGRATION



LOW VOC PAINT



WATER BASED PAINT WITH PURE ACRYLIC POLYMER

## PRODUCT INFORMATION

### PACK SIZES



200 ml

0.9 Ltr

### COVERAGE

WALL

1 COAT

130-150 SFT/Ltr /Coat

2 COATS

65-75 SFT/Ltr /Coat

\*Coverage mentioned is based on lab tests conducted under controlled environment  
\*\*Actual coverage is dependent on factors such as surface condition, application method, and application condition

### UNIQUE FEATURE



Special quality interior paint with metallic finish


### AVAILABLE SHADES

50+\*

\*Currently available through Berger Color Bank



### WASHABILITY



- ✓ HIGH
- MEDIUM
- LOW

## SURFACE PREPARATION



Recommended Surfaces



Concrete Stone



Interior Cement Plaster



Brick Asbestos



Cement Sheet



Surface Preparation Method

After plastering, allow the surface to dry for at least 8-12 weeks. Moisture content should be less than 15%. Before application, ensure that the surface is clean, dry, free from loose particles, dust, dirt, grease, wax, mould, fungal growth, etc. The product should not be applied on surfaces with continuous seepage or dampness.

Berger offers a complete range of surface treatment solutions. Please call 08000-123456 or visit your nearest Berger Experience Zone for more information.



## METHOD OF APPLICATION



Clean surfaces by sanding with emery paper. Fill holes with Robb wall putty



Apply one coat of 100% thinned Robb Water Based Sealer and allow to dry for 4-6 hours



Apply two coats of Robb Wall Putty with a 6-8 hours interval



After overnight drying of putty, sand smooth with emery paper



Apply one coat of 100% thinned Robb Water Based Sealer and let it dry for 4-6 hours



Apply 2-3 coats of Luxury Silk Metallic Finish as finishing coat with a 6-8 hours interval



## MIXING RATIOS



**For Roller** - Paint : Water = 2 : 1  
(By volume)

No dilution needed for application on designs



## ADDITIONAL INFORMATION

- ◆ Use the thinned material within 12 hours
- ◆ Do not retain the thinned material beyond recommended time
- ◆ Do not stretch material beyond recommended coverage
- ◆ Do not apply at temperature below 10°C (50°F)



## ACCOMPANYING PRODUCT



Robbialac Wall Putty



Robbialac Water Sealer



## SHEEN SCALE AND SHADE



## PRODUCT SPECIFICATION




SHADE/  
COLOR

**50+**

\*Currently available through Berger Color Bank




SHELF LIFE



In sealed container kept in cool & dry place



VISCOSITY



TYPE OF  
CURE

Coalescence



PIGMENTATION

METALLIC SILVER

METALLIC GOLD

METALLIC BRONZE



METHOD OF APPLICATION



ROLLER



TOUCH DRY



SOLVENT



WATER



GLYCOL




VOC

≤ 25 g/L

May vary from shade to shade




HARD DRY




\*Total Curing Time: 96 Hours



GLOSS / SHEEN LEVEL



AROMATIC SOLVENT



VEHICLE

Special type acrylic resin emulsions



POT LIFE AFTER THINNING



\*Please refer to MSDS for safety information

The above information is given to the best of our knowledge based on laboratory tests and practical experience. However, since we cannot anticipate or control the many conditions under which our products may be applied, we can only guarantee the quality of the product itself. We reserve the right to alter the given data without prior notice. Covering capacity is indicated on the basis of results obtained on a prepared smooth surface.