



Ultimate painting solution for your dream home

ROBBIALAC WATER SEALER



PRODUCT DESCRIPTION

Robbialac Water Based Sealer is an excellent primer for plastered wall which seals and stops penetration of moisture from inside wall and keeps the topcoat finish unharmed. This primer can also be used on asbestos cement and hard board. Its specially designed formulation confirms the perfect bonding between topcoat and primer to ensure durability of topcoat.



EXCELLENT SUBSTRATE PENETRATION & TOPCOAT ADHESION



ALKALI & EFFLORESCENCE RESISTANCE



LOW VOC AND REDUCES THE GREENHOUSE EMISSIONS



PHYSICAL BARRIER TO SALT MIGRATION

PRODUCT INFORMATION

PACK SIZES



COVERAGE

WALL →

1 COAT
180-200 SFT/Ltr
(Depending upon the surface)

*Coverage mentioned is based on lab tests conducted under controlled environment
**Actual coverage is dependent on factors such as surface condition, application method, and application condition

UNIQUE FEATURE



Water Based Primer based on Acrylic Polymer

SURFACE PREPARATION

Recommended Surfaces

All types of Plasters

Concrete

Asbestos Sheets

Hard Board

False Ceilings

Surface Preparation Method

After plastering, allow the surface to dry for at least 8-12 weeks. Moisture content should be less than 15%. Before application, ensure that the surface is clean, dry, free from loose particles, dust, dirt, grease, wax, mould, fungal growth, etc. The product should not be applied on surfaces with continuous seepage or dampness.

Berger offers a complete range of surface treatment solutions, please call 08000-123456 or visit your nearest Berger Experience Zone for more information.



METHOD OF APPLICATION



Clean surfaces by sanding with emery paper



Apply one coat of 100% thinned Robb Water Based Sealer and allow to dry for 4-6 hours



Apply two coats of Robb Wall Putty with a 6-8 hours interval



After overnight drying of Putty, sand smooth with emery paper



Apply one coat of 100% thinned Robb Water Based Sealer and let it dry for 4-6 hours



MIXING RATIOS



For Brush - Sealer : Water = 1 : 1
For Roller - Sealer : Water = 1 : 1
(By volume)



ADDITIONAL INFORMATION

- ◆ Use the thinned material within 12 hours
- ◆ Do not retain the thinned material beyond recommended time
- ◆ Do not stretch material beyond recommended coverage
- ◆ Do not apply paint at temperature below 10°C (50°F)



ACCOMPANYING PRODUCT



Robbialac Wall Putty



SHEEN SCALE | 2 SHADE

Matt Finish

Egg Shell

Soft Sheen/Satin

High Sheen

Gloss

Super Gloss

***Only available in White**



PRODUCT SPECIFICATION



TYPE OF CURE

Coalescence



SHELF LIFE



In sealed container kept in cool & dry place



VISCOSITY AT 30°C



TOUCH DRY



PIGMENTATION

TITANIUM DIOXIDE

MAGNESIUM SILICATE

ALUMINUM SILICATE



METHOD OF APPLICATION




ROLLER



BRUSH



HARD DRY



SOLVENT



WATER



Ethylene Glycol



VOC

≤ 10 g/L
ISO 11890-2
Might vary shade to shade



POT LIFE AFTER THINNING



AROMATIC CONTENT



Below 50 ppm

*Please refer to MSDS for safety information

The above information is given to the best of our knowledge based on laboratory tests and practical experience. However, since we cannot anticipate or control the many conditions under which our products may be applied, we can only guarantee the quality of the product itself. We reserve the right to alter the given data without prior notice. Covering capacity is indicated on the basis of results obtained on a prepared smooth surface.