

## Technical Information Sheet

### TexBond PD TJ 1335



#### Description:

TexBond PD TJ 1335 is specially designed for high binder loaded recipe where extreme wet & dry rubbing fastness are required. It is specially designed in styrene acrylic system with suitable crosslinking agent. TexBond PD TJ 1335 has been developed with the same principle of Berger to offer products with uncompromising quality. Textile manufacturer can get these products at competitive prices which will match international standards.

TexBond PD TJ 1335 is extremely firm, durable binder due to the presence of cross linked acrylate polymer backbone conferring excellent fastness properties. It does not influence on the efficiency of the viscosity of synthetic thickeners. Its outstanding mechanical stability ensures even distribution and penetration.



#### Physical and Chemical Properties:

Appearance	Milky White Liquid
Smell	Characteristic smell
pH value	(7.5 – 8.5) at 30°C
Viscosity (cps)	Less than 100 cps
Solid Content	(35 ± 1) %
Specific Gravity	(1.030 ± 0.010) at 30°C
Solubility	Can be mixed with water at any ratio
Stability/Compatibility	Very much compatible with the auxiliaries usually applied in printing and dyeing process.
Shelf Life	365 Days (if store in sealed & new container and maintain proper storage condition)



#### Functions:

- Excellent fastness properties
- Specially designed for Panama fabrics
- Compatible for high binder loaded shades
- Contributes a soft handle to the printed material.



#### Film Properties:

After curing produces a dry film which makes the dyestuff pigments appear clear and brilliant.



#### Application Area:

This binder can be used on all kinds of textile materials commonly used in textile printing.



## Handling & Storage:

### Storage

Store in sealed container (HDPE drum or SS container) in dry condition at temperatures between (15 – 30)°C, away from direct heat, sunlight, dust, moisture any sort of chemical's contamination. Equipments used in handling this product can be washed easily with water before it dries up. Hot water with little scrubbing is required to clean the dried product. Containers once opened should be consumed immediately and shut tightly to prevent contamination. Sanitize with sanitization solution after cleaning of used up containers. Stocks should be used on first in and first out basis. Do not mix with other products without consulting R&D or do your test to determine its suitability, as it can lead to incompatibility and other related problems.

### Handling

Transport & storage should be performed under shade, cleaned & closed area and away from heat sources at all time. Use PPE (Hand gloves, Goggles, Cleaned cloth & shoe etc) during filling and transfer to prevent human contact with product. Product's transfer should be performed in clean & properly sanitized transfer lines and pumps.

### Footnote

The information in this TDS is given in good faith and is correct to the best of our knowledge as of the date hereof; however Berger Paints Bangladesh Limited makes no representation to its completeness or accuracy. Customers are requested to evaluate and test the product for their application to find out the suitability before use. Berger Paints Bangladesh Limited disclaims responsibility to damage of any kind resulting from the use of this information.