



Ultimate painting solution for your dream home

WEATHERCOAT ANTIDIRT LONGLIFE



PRODUCT DESCRIPTION

WeatherCoat AntiDirt LongLife is an elastomeric emulsion paint especially formulated for exterior walls due to its unique elastomeric properties, excellent resistance to water, weathering and resistance properties against fungi, algae, and dampness caused by lashing rain. Presence of light fast chemical resistant pigments/fillers, systematic cross-linking of flexible resin binder during drying, special preservatives and other special additives make it an excellent durable coating with retention of color brightness, crack coverage & dirt/stain resistance for a long time.



DURABILITY OF WEATHERCOAT ANTIDIRT LONGLIFE IS 7 YEARS



WATER-BASED PAINT BASED ON ELASTOMERIC POLYMER



EXCELLENT RESISTANCE PROPERTIES AGAINST ALGAE



SUPERIOR UV & WEATHER-ABILITY RESISTANCE



LONG-LASTING DIRT-FREE PROTECTIVE FINISH

PRODUCT INFORMATION

PACK SIZES



0.91 Ltr

3.64 Ltr

18.0 Ltr

AVAILABLE SHADES

5000+*

*Currently available through Berger Color Bank



COVERAGE

WALL

1 COAT

130 – 150 Sft/Ltr /Coat

2 COATS

65 – 75 Sft/Ltr /Coat



*Coverage mentioned is based on lab tests conducted under controlled environment

**Actual coverage is dependent on factors such as surface condition, shade selection, application method, and application condition

UNIQUE FEATURE



DIRT PROTECT FORMULA NANO ADDITIVE



7 YEARS WARRANTY

SURFACE PREPARATION



Recommended Surfaces



Cement Plaster



Brick Asbestos



Cement Sheet



Concrete Stone



All types of Boards



Surface Preparation Method

For new walls: For smooth finish apply two coats of Berger All Purpose Putty with 3 hrs interval directly on plastered surface. After proper drying (24 hrs) of putty, rub down the surface with sandpaper to provide a sound surface for finish coat or apply directly one coat 60-100% thinned W/Coat Exterior Sealer as prime coat. Ensure that the surface is free from loose particles before paint application.

For old walls: Previously painted surface with cement paint should be wire brushed and washed with water. After properly washing of cement paint, 2 coats of Berger All Purpose Putty can be applied (application procedure same like new walls). Or apply directly one coat 60-100% thinned (P:W=1:1) Weather Coat Exterior Sealer as a prime coat. On top of Weather Coat or any kind of emulsion paint, Berger All Purpose Putty cannot be applicable. For recoating on top of emulsion paint apply one coat 60-100% thinned W/Coat Exterior Sealer as a prime coat. Ensure that the surface is free from loose particles before paint application.

Berger offers a complete range of surface treatment solutions, please call 08000-123456 or visit your nearest Berger Experience Zone for more information.



METHOD OF APPLICATION



1
Clean the surface with wire-brush and wash with water. Dry the surface properly



2
Apply WC Exterior Sealer with water by 1 : 1 ratio



3
After 24 hours of applying Berger WC Exterior Sealer apply 2 coats of Touch Putty with 3 hours interval



4
Wait for 24 hours after applying 2 coats of putty. Then apply two coats of Weather Coat Anti Dirt Long Life with 24 hours interval



MIXING RATIOS



For Brush - Paint : Water = 2 : 1
For Roller - Paint : Water = 3 : 1
(By volume)



ADDITIONAL INFORMATION

- ◆ Use the thinned material within 12 hours
- ◆ Do not retain the thinned material beyond the recommended time
- ◆ Do not stretch material beyond recommended coverage
- ◆ Do not apply paint at a temperature below 10°C (50°F)



RECOMMENDED UNDERCOATS



WC Touch Putty



Weather Coat Exterior Sealer



SHEEN SCALE



PRODUCT SPECIFICATION




SHADE/
COLOR

5000+*


*Currently available through Berger Color Bank




SHELF LIFE



VISCOSITY AT
30°C



GLOSS/SHEEN
LEVEL




PIGMENTATION

TITANIUM DIOXIDE | MAGNESIUM SILICATE
ALUMINIUM SILICATE




METHOD OF
APPLICATION



ROLLER | BRUSH



TOUCH DRY



TYPE OF CURE

Coalescence




VOC

≤ 25 g/L
ISO 11890-2
Might vary shade to shade



HARD DRY



CLEAN UP
SOLVENT



WATER



VEHICLE

Special type Elastomeric acrylic resin emulsions

*Please refer to MSDS for safety information

The above information is given to the best of our knowledge based on laboratory tests and practical experience. However, since we cannot anticipate or control the many conditions under which our products may be applied, we can only guarantee the quality of the product itself. We reserve the right to alter the given data without prior notice. Covering capacity is indicated based on results obtained on a prepared smooth surface.