



Ultimate painting solution for your dream home

WEATHERCOAT ANTIDIRT SUPREME TOP COAT



PRODUCT DESCRIPTION

WeatherCoat Antidirt Supreme Top Coat is a water-based exterior paint formulated with a special type of pure acrylic polymer that produces a saturated film over the substrate to offer high performance against dirt picking tendency and gives a freshly painted look for a long time. It has outstanding durability with special fungicide and algacide to control surface growth. It's special Nano Additive Technology offers a better shiny look with excellent weatherproofing against UV rays & the acidic gases in the atmosphere. WC Antidirt Supreme Top Coat is a combined pack with WC Antidirt Supreme base coat for better durability & longevity.



LONG LASTING
DIRT FREE
PROTECTIVE FINISH



SPECIAL NANO ADDITIVE
TECHNOLOGY



LOW VOC



EXCELLENT
WATERPROOFING



PROTECTION
AGAINST
HAIRLINE CRACK

PRODUCT INFORMATION

PACK SIZES



0.91 Ltr

3.64 Ltr

18.0 Ltr

COVERAGE

WALL

1 COAT

130-140 SFT/Ltr

2 COATS

65-70 SFT/Ltr



UNIQUE FEATURE

10 YEARS DURABILITY WARRANTY
No Hairline Crack (<0.6mm)

5 YEARS WATERPROOFING WARRANTY
Anti-Fungal Property

AVAILABLE SHADES

5000+*

*Currently available through Berger Color Bank



*Coverage mentioned is based on lab tests conducted under controlled environment
**Actual coverage is dependent on factors such as surface condition, application method, and application condition

SURFACE PREPARATION



Recommended Surfaces



Plasters



Concrete



Brick



Cement Sheet



All types of building



Surface Preparation Method

For new walls: It is advisable to allow newly plastered surfaces to mature for only a period of 3 to 4 months. Ensure that the surface is free from loose particles and any greasy/oily substance by cleaning the surface through rubbing with emery paper or wire brush. Then treat the surface as a requisite with Mr. Expert Salt Wash.

For old walls: In case of repainting job, previous coatings of lime wash/loosely bonded emulsion-based paint must be scraped off. Earlier coatings of emulsion-based paint need not to be removed if it is in sound condition. However, the gloss of the sheen of such coatings must be removed by thorough sanding. Cracked or flaked paint must be removed completely. Fungus-affected areas need separate adequate treatment. Repair the cracked portion of plasters and areas (affected by leaks, drainage etc) properly with crack filler paste prior to painting. Allow the surface to dry sufficiently.

Berger offers a complete range of surface treatment solutions, please call 08000-123456 or visit your nearest Berger Experience Zone for more information.



METHOD OF APPLICATION



Scrub clean with sandpaper



If the wall is affected by salt, wash the surface with Mr. Expert Salt Wash



Apply 2 coats of Antidirt Supreme Basecoat maintaining 6-8 hours interval between the coats



If the paint surface has holes on it, apply WeatherCoat Touch Putty in between the base coat.



Apply 2 coats of Basecoat and dry for 12 hours



Apply 2 coats of Antidirt Supreme Topcoat maintaining 6-8 hours interval between the coats



MIXING RATIOS



For Brush - Paint : Water = 2 : 1
For Roller - Paint : Water = 3 : 1
(By volume)



ADDITIONAL INFORMATION

- Use the thinned material within 12 hours
- Do not retain the thinned material beyond the recommended time
- Do not stretch material beyond recommended coverage
- Do not apply paint at a temperature below 10°C (50°F)



RECOMMENDED UNDERCOATS



Sheen Scale



All Purpose Putty



WC Antidirt supreme base coat



PRODUCT SPECIFICATION




SHADE/
COLOR

5000+*

*Currently available through Berger Color Bank



SHELF LIFE




In sealed container kept in cool & dry place



VISCOSITY AT
30°C



GLOSS / SHEEN
LEVEL



AT 85°



PIGMENTATION

TITANIUM DIOXIDE MAGNESIUM SILICATE ALUMINUM SILICATE



METHOD OF
APPLICATION



ROLLER BRUSH



TOUCH DRY



SOLVENT



WATER



ETHYLENE
GLYCOL



VOC

≤ 25 g/L

ISO 11890-2

Might vary from shade to shade



HARD DRY



(Recoat)



Coating Interval



VEHICLE

Specially featured
Acrylic Emulsion



TYPE OF
CURE

Coalescence



POT LIFE
AFTER
THINNING



*Please refer to MSDS for safety information

The above information is given to the best of our knowledge based on laboratory tests and practical experience. However, since we cannot anticipate or control the many conditions under which our products may be applied, we can only guarantee the quality of the product itself. We reserve the right to alter the given data without prior notice. Covering capacity is indicated based on results obtained on a prepared smooth surface.