



Ultimate painting solution for your dream home

WEATHERCOAT GLOW



PRODUCT DESCRIPTION

WEATHERCOAT GLOW is an especially formulated flexible gloss coating for exterior walls. Due to its unique shiny appearances it gives your walls a vibrant look with extra water repellency and resistance properties against fungi, algae, and dampness. This coating maintains a high degree of elasticity over time, which allows the paint film to be free from the hair cracks due to the concrete shrinkage.



WATERPROOFING AND WATER REPELLENCY



RESISTANCE AGAINST ALGAE, FUNGI



PROTECTION AGAINST HAIRLINE CRACK



SUPERB ALKALI & EFFLORESCENCE RESISTANCE



PRODUCT INFORMATION

PACK SIZES



COVERAGE

SURFACE

1 COAT
160-170 Sft/L /Coat

(Depending upon the surface)



UNIQUE FEATURE



HIGH SHEEN



WATERPROOFING & WATER REPELLENCY

AVAILABLE SHADES

2000+*



*Currently available through Berger Color Bank

*Coverage mentioned is based on lab tests conducted under controlled environment
**Actual coverage is dependent on factors such as surface condition, shade selection, application method, and application condition

SURFACE PREPARATION



Recommended Surfaces



Cement plaster



Concrete stone



Brick asbestos



Cement Sheet



All types of building Boards



Surface Preparation Method

Surface must be clean, free from dust, grease, oil, heavy soot, chalk, mildew, etc. Calk joints and fill holes where necessary. All old loose, flaking or peeling paint must be removed.

Surface preparation for new walls: For smooth finish apply two coats of Robb. All Purpose Putty White with 3 hrs interval directly on plastered surface. After proper drying (24 hrs) of putty, rub down the surface with sandpaper to provide a sound surface for finish coat. Apply one coat 60-100% thinned (P:W=1:1) W/Coat Exterior Sealer as prime coat. Ensure that the surface is free from loose particles before paint application.

Surface preparation for Old/Previously painted walls: Apply directly one coat 60-100% thinned (P:W=1:1) Weather Coat Exterior Sealer as prime coat on top of Weather Coat or any kind of emulsion paint. Application of Weather Coat Touch Putty to make the wall smooth through filling holes and pits. Before application of topcoat, smoothen the wall using emery paper ~200 mesh.



METHOD OF APPLICATION



Clean the surface with wire-brush and wash with water. Dry the surface properly



Apply one coat of WC Exterior Sealer



After applying WC Exterior Sealer, apply 2 coats of All Purpose Putty



Wait for 6 hours after applying 2 coats of All Purpose Putty. Then apply 2-3 coats of Weather Coat Glow as top coat with 24 hours interval



MIXING RATIOS



For Brush - Paint : Water = 2 : 1
For Roller - Paint : Water = 2 : 1
(By volume)



ADDITIONAL INFORMATION

- ◆ Use the thinned material within 12 hours
- ◆ Do not retain the thinned material beyond recommended time
- ◆ Do not stretch material beyond recommended coverage
- ◆ Do not apply paint at temperature below 10°C (50°F)



RECOMMENDED UNDERCOATS



SHEEN SCALE



Berger All Purpose Putty



Weather Coat Exterior Sealer



PRODUCT SPECIFICATION



SHADE/
COLOR

2000+*

*Currently available through Berger Color Bank



PIGMENTATION

TITANIUM
DIOXIDE

MAGNESIUM
SILICATE


ALUMINIUM
SILICATE



VISCOSITY AT
30°C



GLOSS / SHEEN
LEVEL



SOLVENT



WATER



ETHYLENE
GLYCOL



METHOD OF
APPLICATION



ROLLER



BRUSH



TOUCH DRY



% TOTAL SOLIDS
(WEIGHT)

50




VOC

≤ 15 g/L
(Depending on Shades)



HARD DRY



% TOTAL SOLIDS
(VOLUME)

~38

*Please refer to MSDS for safety information

The above information is given to the best of our knowledge based on laboratory tests and practical experience. However, since we cannot anticipate or control the many conditions under which our products may be applied, we can only guarantee the quality of the product itself. We reserve the right to alter the given data without prior notice. Covering capacity is indicated on the basis of results obtained on a prepared smooth surface.