

Ultimate painting solution for your dream home

WeatherCoat Exterior Sealer



PRODUCT DESCRIPTION

WeatherCoat Exterior Sealer is an excellent primer for plastered wall, which seals porosity of the surface and prevent evaporation of moisture from an inside wall and keeps the topcoat finish safe and sound. This primer can also be used on asbestos cement and hard board.



THIS IS BASED ON PURE
ACRYLIC POLYMER



EXCELLENT SUBSTRATE
PENETRATION &
TOPCOAT ADHESION



PRODUCT INFORMATION

PACK SIZES



3.64 Ltr

18.2 Ltr

COVERAGE

WALL

1 COAT

160-170 SFT/
Ltr/Coat

*Coverage mentioned is based on lab tests conducted under controlled environment

**Actual coverage is dependent on factors such as surface condition, application method, and application condition

UNIQUE FEATURE



SURFACE PREPARATION



Recommended Surfaces



Concrete



Hard Board



Asbestos Sheets



All types
of Plasters



Surface Preparation
Method

SURFACE PREPARATION: Surface must be clean, free from dust, grease, oil, heavy soot, chalk, mildew, etc. Chalk joints and fill holes where necessary. All old loose, flaking or peeling paint must be removed.

For New walls: Before application of Weather Coat Exterior Sealer, for smooth finish apply two coats of Berger All Purpose putty White with 3 hrs interval directly on plastered surface. After proper drying (24 hrs) of A/P putty white, rub down the surface with sandpaper to provide a sound surface for a prime coat.

For Old walls: Previously painted surface with cement paint should be wire brushed and washed with water. And previously painted Weather Coat / any emulsion surface must be wire brushed and cleaned thoroughly.

Berger offers a complete range of surface treatment solutions, please call 08000-123456 or visit your nearest Berger Experience Zone for more information.



METHOD OF APPLICATION



Mix the Weather Coat Exterior Sealer in the ratio of 60 : 100% with water



Apply the mixture as primary coat before painting



Don't leave out the mixed sealer for more than 12 hours



MIXING RATIOS



For Brush - Paint : Water = 1 : 1
For Roller - Paint : Water = 1 : 1
(By volume)



ADDITIONAL INFORMATION

- ◆ If there is salt in the wall or there exists any algae/fungus on it, special treatment is required
- ◆ Do not apply at a temperature below 10°C (50°F)



ACCOMPANYING PRODUCT



All Purpose Putty



SHEEN SCALE AND SHADE

Matt

Egg Shell

Soft Sheen/Satin

High Sheen

Gloss

Super Gloss

***Only available in White**



PRODUCT SPECIFICATION




TYPE OF CURE

Coalescence



SHELF LIFE



VISCOSITY AT 30°C



TOUCH DRY



PIGMENTATION

TITANIUM DIOXIDE MAGNESIUM SILICATE ALUMINUM SILICATE



METHOD OF APPLICATION



ROLLER

BRUSH



HARD DRY



SOLVENT



WATER



% OF TOTAL SOLIDS (WEIGHT)

46.0



VOC

≤ 25 g/L



VEHICLE

Special type Acrylic Resin Emulsions

*Please refer to MSDS for safety information

The above information is given to the best of our knowledge based on laboratory tests and practical experience. However, since we cannot anticipate or control the many conditions under which our products may be applied, we can only guarantee the quality of the product itself. We reserve the right to alter the given data without prior notice. Covering capacity is indicated based on results obtained on a prepared smooth surface.